

1. Product-type:  
HPL composite panel reference DRY INTERNAL F (Thickness: 14 - 26 mm)
2. Name & contact address of the manufacturer:  
Parklex International,s.l.  
Polígono Alkaiga, C/Baldrun 1  
31.780 Bera – Navarra (Spain)
3. Intended use of the construction product:  
As internal finishes in walls or ceilings, subject to reaction to fire regulations
4. System of assessment and verification of the constancy of performance: 1
5. Notified body:
  - Tecnalía R&I Certificación NB 1239
  - Evaluation of the Factory Production Control
  - Reaction to fire for initial type testing
  - System 1
  - Certificate of constancy of performance of the product Nº 1239/CPR/ 0801003 dated June 30, 2006

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	B-s2;d0	EN 438-7:2005
Resistance to fire	NPD	
Water vapour permeability	NPD	
Resistance to fixings thickness ≤ 15 mm thickness > 15 mm	≥ 100 N/mm ≥ 1.500 N	
Direct airborne sound insulation	NPD	
Bonding Strength	≥ 1MPa	
Flexural tensile strength	≥ 1MPa	
Thermal conductivity	NPD	
Content of pentachlorophenol	< 5 ppm	
Release of formaldehyde	Class E1	
Sound absorption	NPD	
Thermal shock resistance	NPD <sup>1</sup>	
Durability: Glue-line quality	Grade 3	
Durability: Resistance to elevated temperature	No visible change	
Durability: Resistance to wet conditions	≤ 5%	

<sup>1</sup> Applicable only to panels intended for external use

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Rodrigo (General Director)

Signature:

Place and date of issue:

  
www.parklex.com

Bera April 30, 2019