

## DECLARATION OF PERFORMANCE Nº 2014050804

1. Product-type:  
High Pressure compact laminate reference WET INTERNAL S (Thickness: 6 - 22 mm)
2. Name & contact address of the manufacturer:  
Parklex International,s.l.  
Polígono Alkaiga, C/Baldrun 1  
31.780 Bera – Navarra (Spain)
3. Intended use of the construction product:  
As internal finishes in walls or ceilings, subject to reaction to fire regulations
4. System of assessment and verification of the constancy of performance: 3
5. Notified body:
  - Tecnalía Research & Innovation NB 1292
  - Reaction to fire for initial type testing
  - System 3

### 6. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications	
Reaction to fire	C-s1;d0	EN 438-7:2005	
Resistance to fire	NPD		
Water vapour permeability	Wet cup		110
	Dry cup		250
Resistance to fixings	6mm thickness		2.000 N
	8 mm thickness		3.000 N
	≥ 10 mm thickness		4.000 N
Direct airborne sound insulation	NPD		
Bonding Strength	NPD <sup>1</sup>		
Flexural tensile strength	PASS		
Thermal conductivity	NPD		
Content of pentachlorophenol	NPD <sup>1</sup>		
Release of formaldehyde	CLASS E1		
Sound absorption	NPD		
Thermal shock resistance	NPD <sup>2</sup>		
Durability: Immersion in boiling water	PASS		
Durability: Density	PASS		

<sup>1</sup> Applicable only to HPL composite panels

<sup>2</sup> Applicable only to panels intended for external use

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Rodrigo (General Director)

Signature:

Place and date of issue:

**Parklex®**  
www.parklex.com



Bera, the 31<sup>st</sup> of May 2017